

BIOCLEAN-D DROP-DOWN Sterile Garment with Hood S-BDSH

About

The BioClean-D Drop-down Garment with Hood is a sterile antistatic disposable garment manufactured from low-linting CleanTough material. Its unique design offers true aseptic donning, with internal coloured tabs to indicate safe touch points to prevent touching the outside surface. The innovative up and over donning design eliminates the risk of the garment touching the floor, and strategically placed quick release tabs (to hold and remove during zip closure) ensure aseptic donning through out the donning process.

Specifications

MATERIAL:

Antistatic BioClean-D CleanTough white material

COLOUR:

White

CONSTRUCTION:

Bound seams with single needle stitching

CHARACTERISTICS:

Antistatic to EN 1149-5* & low particulating

COMPATIBILITY:

ISO Class 4 & EU GMP Grade A

STERILIZATION:

Gamma irradiation

Features

- Elasticated back, hood, cuffs and ankles
- Foot-loop to aid smooth closure of zip
- Thumb loops to ensure a secure hold
- Quick release press stud tabs for aseptic donning
- Low-linting CleanTough material



EXCEPTIONAL
COMFORT AND
PROTECTION

ANTISTATIC & LOW-
LINTING

UNIQUE UP AND OVER
DESIGN

ASEPTIC DONNING
TECHNIQUE



Quality Standards

- Manufactured in a facility holding ISO 9001:2008
- Tested against permeation standard ASTM F739-12
- Processed in an NEBB certified ISO Class 4 environment
- Tested against standards: EN 1149-5*, protective clothing - electrostatic properties; EN 530, Abrasion resistance; EN 7854, Flex cracking resistance; EN 6530, Resistance to penetration by liquids; EN 13934-1, Tensile strength; EN 9073-4, Trapezoidal tear resistance; EN 863, Puncture resistance; and EN 13935-2, Seam strength
- Sterilized in accordance with ISO 11137-1:2006

Sterilization

Method: Gamma irradiation
 Minimum Dose: 25kGy
 Sterility Assurance Level: 10^{-6}

Shelf Life & Storage

Three (3) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

Performance Test Results – BioClean-D CleanTough White Material

TEST	RESULT		PERFORMANCE CLASS (EN 14325)
Abrasion Resistance	10 to 100 cycles		1
Flex Cracking Resistance	5,000 to 15,000 cycles		3
Trapezoidal Tear Resistance	MD 55.5 N		3
Trapezoidal Tear Resistance	CD 29.3 N		2
Tensile Strength	MD 97 N		2
Tensile Strength	CD 48 N		1
Puncture Resistance	8 N		1
Repellence to Liquids	30% H ₂ SO ₄	96.3%	3
	10% NaOH	97.6%	3
	O-Xylene	95.7%	3
	Butan-1-ol	96.6%	3
Penetration by Liquids	30% H ₂ SO ₄	0%	3
	10% NaOH	0%	3
	O-Xylene	0%	3
	Butan-1-ol	0%	3
Seam Strength ²	70 N		2
Electrostatic Charge Half Decay Time, t_{50} (secs)	0.07		PASS

Particle Shedding Test Results

TEST	RESULT	CATEGORY (IEST-RP-CC003.3)
Particle Shedding (Helmke Drum Test)	<2000	Category I

BioClean-D™ CleanTough White Material - ASTM F739-12 Test Method Results

Mean Breakthrough Time (MBT), Minutes

Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.1 µg/cm²/min

CISPLATIN	CARMUSTINE	CYCLO- PHOSPHA- MIDE	DOXO- RUBICIN HYDRO- CHLORIDE	5- FLUORO- URACIL	METHO- TREXATE	ETOPOSIDE	PACLITAXEL	THIOTEPA
>240	<6	217 (275,162,215)	>240	>240	>240	>240	<10	30 (28,30,33)

Results achieved under controlled laboratory conditions, by accredited external testing laboratory.

TO ORDER

Re-Order	Chest	Height	Size
S-BDSH-XS	76-84cm (30"-33")	158-164cm (5'2"-5'4")	X-Small
S-BDSH-S	84-92cm (33"-36")	164-170cm (5'4"-5'6")	Small
S-BDSH-M	92-100cm (36"-39")	170-176cm (5'6"-5'9")	Medium
S-BDSH-L	100-108cm (39"-42")	176-182cm (5'9"-6'0")	Large
S-BDSH-XL	108-116cm (42"-45")	182-188cm (6'0"-6'2")	X-Large
S-BDSH-XXL	116-124cm (45"-48")	188-194cm (6'2"-6'4")	XX-Large
S-BDSH-XXXL	124-132cm (48"-51")	194-200cm (6'4"-6'6")	XXX-Large
S-BDSH-XXXXL	132-140cm (51"-54")	200-206cm (6'6"-6'8")	XXXX-Large
S-BDSH-5XL	140-148cm (54"-57")	206-212cm (6'8"-6'10")	5X-Large
S-BDSH-6XL	148-156cm (58"-61")	212-218cm (6'10"-6'12")	6X-Large
S-BDSH-7XL	156-164cm (61"-64")	218-224cm (7'1"-7'3")	7X-Large
S-BDSH-8XL	164-172cm (64"-67")	224-230cm (7'3"-7'5")	8X-Large

Packing

One piece per sealed inner PE bag; one inner bag per sealed outer PE bag; 20 outer bags per per lined carton (20 pieces).

Please note: sizes XXXL, XXXXL, 5XL, 6XL, 7XL & 8XL 15 coveralls per carton.

Sizes XXXXL, 5XL, 6XL, 7XL & 8XL subject to minimum order quantity and extended lead time.

*NOTE: BioClean CleanTough material is static dissipative and, with a charge half decay time of 0.07 sec, and so are ideal for use in a static-safe environment

For additional information visit us at www.bioclean.com, or call us at +44 1638 663338

Nitritex Ltd
Minton Enterprise Park
Oaks Drive
Newmarket, Suffolk
CB8 7YY
United Kingdom

S-BDSH/1810/PDS25

Ansell

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell

assumes no responsibility for the suitability or adequacy of an end user's selection of disposable garments for a specific application.

**Please see product validation pack or contact Ansell customer service for specific data on use of garments with cytotoxic drugs. Garments used for protection against such drugs must be selected specifically for the type of chemicals used.

Ansell, ® and TM are trademarks owned by Ansell Limited or one of its affiliates. © 2012 – 2018 Ansell Limited. All Rights Reserved.