bimos

characteristics Cleanroom Stool 3 with glides and footring

Article: 9469R artificial leather

	Seat:	H:	570-850
		B:	400
		T:	400
Packing data	10/aight	ka	8,5
T acking data	Weight	kg	0,0
	Volume	m³	0,13



Base equipment		Benefit
Suitability for cleanrooms	Air purity level 3 according to DIN EN ISO 14644-1	Certified suitability for clean rooms
	Air purity level 1 according to US-Fed St. 209E Sealed upholstery with special foam	It can be ensured that no particles are emitted
	technology	The build-up of particles on the chair are avoided
	Materials that are suitable for use in clean rooms	
Conductivity	Smooth, sealed surfaces The metal components have a conductive	Exceeds the requirements of ESD protection according
	coating Volume conductive plastic parts	to standard DIN EN 61340-5-1
	The high-comfort upholstery is also conductive Typical discharge resistance of 10 ⁶ Ohm	100% ESD protection
Seat	Conductive glides Extra large seat with a diameter of 400 mm	Automatically encourages healthy posture and upright
		seating The round front edge of the seat prevents blocked circulation in the thighs
Finishes for seat	ESD synthetic leather upholstery:	The soft and comfortable upholstery provides a
	High-level ESD synthetic leather Skai Tundra. Resistant to desinfectants, washable and	comfortable feel. However, damages caused by sharp parts can not be
	easy-care	excluded.
Seat height	Colour: black (2571) Stepless seat height setting from 570-850 mm	Ideal for the use in production and laboratory Seat height can be adapted to nearly 95% of all body
Gearneight	supported by safety gas spring with protective cover	sizes, the cover protects the gas spring from dust and dirt
Functions / Mechanism	Ring release	Height adjustment can be operated comfortable and easy in sitting position
Base	The chairs are supplied with a brilliantly polished and wearproof aluminium 5 star base	Very high stability, longevity
Glides	Wearproof plastic glides with a large surface area. Conductive	Offer a superb level of stability
foot ring	Chrome-plated foot ring, adjustable in height	Provides support through the wide tread area and can be easily and quickly adjusted in height
Materials	The materials used are recyclable	Environmentally friendly
Standards	DIN EN ISO 14644-1	Certified suitability for clean rooms
	DIN 61340-5-1 DIN 68 877	100% ESD protection Procuring is insured
	German GS "safety tested" mark of confirmity	
	Quality Management System DIN EN ISO 9001	
	Regulation EWG Nr. 1836/93	
	Environmental Management System DIN EN	

bimos

characteristics Cleanroom Stool 3 with glides and footring

Article: 9469R artificial leather

Dimensions in mm			
	Seat:	H:	570-850
		В:	400
		T:	400
Packing data	Weight	kg	8,5
	Volume	m³	0,13



Warranty

10 year long term warranty, 3 years full warranty

Guaranteed quality and high efficiency